



Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

DOCUMENT GROUP: CERAMIC/REPAIR/SYSTEMS VERSION REF: 11635/UPS210CR
DATE: 1ST FEBRUARY 2018 VERSION NO: 2.00
REVISION DATE: 1ST FEBRUARY 2019 SUPERSEDES DATE: 1ST NOVEMBER 2016

MATERIAL SAFETY DATA SHEET

UPS 210 CR EFFICIENCY FLUID CERAMIC KIT

MANUFACTURER:
UNIQUE POLYMER SYSTEMS LTD,
UNIT 19, LINK BUSINESS CENTRE,
LINK WAY, MALVERN, WORCESTERSHIRE
WR14 1UQ
, UNITED KINGDOM
TELEPHONE NUMBER: +44 (0) 1531 63 63 00
EMAIL: SALES@UNIQUEPOLYMERSYSTEMS.COM

EMERGENCY TELEPHONE NUMBER: +44 (0) 1531 63 63 00

THIS PRODUCT IS A KIT AND SUPPLIED AS A MULTI PART PRODUCT WHICH CONSISTS OF A BASE COMPONENT AND ACTIVATOR COMPONENT. THIS DOCUMENT CONTAINS THE MSDS FOR BOTH BASE AND ACTIVATOR COMPONENTS.

TRANSPORTATION INFORMATION

ACTIVATOR	BASE
UN number: UN2735 UN proper shipping name Shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (4-TERT-BUTYLPHENOL) Transport class: 814.4. Packing group: III Environmental hazards Environmentally hazardous: Yes Marine pollutant: No Special precautions for user Special precautions: No special precautions. Tunnel code: E Transport category: 3	UN number: UN3077 UN proper shipping name Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. Transport class: 9 Packing group Packing group: III Environmental hazards Environmentally hazardous: Yes Marine pollutant: Yes Special precautions for user Special precautions: No special precautions. Tunnel code: E Transport category: 3

DISCLAIMER: The information supplied in the MSDS is correct at the time of writing and date of issue. No warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for particular purpose or course of performance or usage of trade. The user of the material is responsible for ensuring the suitability of this product for application.

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of Substance/ Preparation and Company

- 1.1 Product identifier
UPS 210 CR EFFICIENCY FLUID CERAMIC ACTIVATOR
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
Aliphatic polyamine hardener blend with inert fillers for repairing metalwork
- 1.3 Details of the supplier of the safety data sheet
Unique Polymer Systems LTD,
Unit 19, Link Business Centre,
Link Way, Malvern, Worcestershire,
WR14 1UQ Tel: +44 (0) 1531 63 63 00
Email: sales@uniquepolymersystems.com
- 1.4 Emergency telephone number
+44 (0) 1531 63 63 00 (9am to 5pm)

Section 2: Hazards identification

2.1. Classification of the substance or mixture
Classification under CHIP: Xn: R20/21/22; C: R34; Sens.: R43; N: R51/53; Xn: R62
Classification under CLP: Acute Tox. 4: H302; Aquatic Chronic 3: H412; Repr. 2: H361f; Skin Corr. 1B: H314; Skin Sens. 1A: H317

Most important adverse effects: Harmful by inhalation, in contact with skin and if swallowed. Causes burns. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Possible risk of impaired fertility.

2.2. Label elements

Label elements:

Hazard statements: H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H361f: Suspected of damaging fertility.

H412: Harmful to aquatic life with long lasting effects.

Signal words: Danger

Hazard pictograms: GHS05:

Corrosion

GHS07: Exclamation mark

GHS08: Health hazard



Precautionary statements: P102: Keep out of reach of children.

P202: Do not handle until all safety precautions have been read and understood.

P260: Do not breathe vapours.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302+352: IF ON SKIN: Wash with plenty of water/.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+313: If skin irritation or rash occurs: Get medical advice/attention.

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

P501: Dispose of contents/container to hazardous or special waste collection point.

Label elements under CHIP:

Hazard symbols: Corrosive.

Dangerous for the environment.



Risk phrases: R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.

R34: Causes burns.

R43: May cause sensitisation by skin contact.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R62: Possible risk of impaired fertility.

Safety phrases: S1/2: Keep locked up and out of the reach of children.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S29: Do not empty into drains.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BENZYL ALCOHOL

EINECS	CAS	CHIP Classification	CLP Classification	Percent
202-859-9	100-51-6	Xn: R20/22	Acute Tox. 4: H332; Acute Tox. 4: H302	10-30%

4-TERT-BUTYLPHENOL

202-679-0	98-54-4	Xi: R38; Xi: R41; Xn: R62	Repr. 2: H361f; Skin Irrit. 2: H315; Eye Dam. 1: H318	10-30%
-----------	---------	---------------------------	---	--------

M-PHENYLENEBIS(METHYLAMINE)

216-032-5	1477-55-0	C: R34; Xn: R20/22; Sens.: R43	Skin Corr. 1B: H314; Acute Tox. 4: H302; Skin Sens. 1: H317; Aquatic Chronic 3: H412; Acute Tox. 4: H332	10-30%
-----------	-----------	--------------------------------	--	--------

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

220-666-8	2855-13-2	Xn: R21/22; C: R34; Sens.: R43; -; R52/53	Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Aquatic Chronic 3: H412	1-10%
-----------	-----------	---	---	-------

TRIMETHYLHEXANE-1,6-DIAMINE

247-063-2	25513-64-8	C: R34; Xn: R22; Sens.: R43	Skin Corr. 1C: H314; Acute Tox. 4: H302; Skin Sens. 1A: H317; Aquatic Chronic 3: H412; Acute Tox. 4: H312	1-10%
-----------	------------	--------------------------------	--	-------

PHENOL, STYROLISED

262-975-0	61788-44-1	Xi: R38; Sens.: R43; N: R51/53	Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	1-10%
-----------	------------	-----------------------------------	---	-------

SALICYLIC ACID

200-712-3	69-72-7	Xn: R22; Xi: R41	Eye Dam. 1: H318; Acute Tox. 4: H302+332	1-10%
-----------	---------	------------------	--	-------

REACTION PRODUCT FROM 1,3-BENZYL DIMETHANAMINE AND BISPHENOL A EPICHLOROHYDRIN

-	113930-69-1	Xn: R22; Sens.: R43; N: R51/53	Aquatic Chronic 2: H411; Acute Tox. 4: H302; Skin Sens. 1: H317	1-10%
---	-------------	-----------------------------------	--	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary.

If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Amber

Odour: Ammoniacal

Solubility in water: Insoluble

Viscosity: Non-viscous

Boiling point/range°C: >200 Flash point°C: >100

Autoflammability°C: 380 Relative density: 1.0

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

BENZYL ALCOHOL

IVN	RAT	LD50	53	mg/kg
OEL	MUS	LD50	1360	mg/kg
ORL	RAT	LD50	1230	mg/kg

M-PHENYLENEBIS(METHYLAMINE)

DERMAL	RAT	LD50	31000	mg/kg
ORAL	RAT	LD50	930	mg/kg

TRIMETHYLHEXANE-1,6-DIAMINE

DERMAL	RAT	LD50	1280	mg/kg
ORAL	RAT	LD50	910	mg/kg

PHENOL, STYROLISED

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

SALICYLIC ACID

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	891	mg/kg

Relevant effects for mixture:

Effect	Route	Basis
Acute toxicity (harmful)	INH DRM ING	Hazardous; calculated
Corrosivity	OPT INH DRM	Hazardous calculated
Sensitisation	DRM	Hazardous; calculated
Toxicity for reproduction	-	Hazardous; calculated

Symptoms / routes of exposure

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

M-PHENYLENEBIS(METHYLAMINE)

DAPHNIA	48H EC50	15.2	mg/l
FISH	96H LC50	>100	mg/l

RIMETHYLHEXANE-1,6-DIAMINE

FISH	48H EC50	174	mg/l
------	----------	-----	------

PHENOL, STYROLISED

DAPHNIA	48H EC50	1-10	mg/l
FISH	96H LC50	14.8	mg/l

SALICYLIC ACID

FISH	48H EC50	1380	mg/l
------	----------	------	------

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN2735

14.2. UN proper shipping name

Shipping name: AMINES, LIQUID, CORROSIVE, N.O.S.
(4-TERT-BUTYLPHENOL)

14.3. Transport hazard class(es)

Transport class: 814.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

H302+332: Harmful if swallowed or if inhaled.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H332: Harmful if inhaled.

H361f: Suspected of damaging fertility.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Unique Polymer Systems LTD


Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.
R20/22: Harmful by inhalation and if swallowed.
R21/22: Harmful in contact with skin and if swallowed.
R22: Harmful if swallowed.
R34: Causes burns. R38: Irritating to skin.
R41: Risk of serious damage to eyes.
R43: May cause sensitisation by skin contact.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R62: Possible risk of impaired fertility.

DISCLAIMER: The information supplied in the MSDS is correct at the time of writing and date of issue. No warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for particular purpose or course of performance or usage of trade. The user of the material is responsible for ensuring the suitability of this product for application.



DISCLAIMER: The information supplied in the MSDS is correct at the time of writing and date of issue. No warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for particular purpose or course of performance or usage of trade. The user of the material is responsible for ensuring the suitability of this product for application.

SECTION 1: Identification of Substance/ Preparation and Company

1.2 Product identifier

Unique Polymer Systems LTD
Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00
sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

UPS 210 CR EFFICIENCY FLUID CERAMIC BASE

- 1.2 Relevant identified uses of the substance or mixture and uses advised against
Aliphatic polyamine hardener blend with inert fillers for repairing metalwork
- 1.3 Details of the supplier of the safety data sheet
Unique Polymer Systems LTD,
Unit 19, Link Business Centre,
Link Way, Malvern, Worcestershire,
WR14 1UQ Tel: +44 (0) 1531 63 63 00
Email: sales@uniquepolymersystems.com
- 1.4 Emergency telephone number
+44 (0) 1531 63 63 00 (9am to 5pm)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: Xi: R36/38; Sens.: R43; N: R51/53

Classification under CLP: Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317

Most important adverse effects: Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

Signal words: Warning

Hazard pictograms:

GHS07: Exclamation mark

GHS09: Environmental



Precautionary statements: P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.

P264: Wash skin thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321: Specific treatment (see information on this label).

Label elements under CHIP:

Hazard symbols: Irritant.


Dangerous for the environment.

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.



Risk phrases: R36/38: Irritating to eyes and skin.

R43: May cause sensitisation by skin contact.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S2: Keep out of the reach of children.

S24: Avoid contact with skin.

S29: Do not empty into drains.

S37: Wear suitable gloves.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

EINECS	CAS	CHIP Classification	CLP Classification	Percent
500-033-5	25068-38-6	Xi: R36/38; Sens.: R43; N: R51/53	-Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	10-30%

BISPHENOL F TYPE EPOXY RESIN

EINECS	CAS	CHIP Classification	CLP Classification	Percent
500-108-2	28064-14-4	Xi: R36/38; N: R51/53; Sens.: R43	Skin Irrit. 2: H315; Eye Irrit. 2: H319; Skin Sens. 1: H317; Aquatic Chronic 2: H411	10-30%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not create dust.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of dust in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Respiratory protective device with particle filter.

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Prevent from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste

Colour: Various

Odour: Barely perceptible odour

Evaporation rate: Negligible

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Viscosity: Highly viscous

Boiling point/range°C: >200 Flash point°C: >150

Relative density: 1.7g/cc

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
ORAL	RAT	LD50	>2000	mg/kg
ORAL	RBT	LD50	>2000	mg/kg

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

ORL	MUS	LD50	15600	mg/kg
ORL	RAT	LD50	11400	mg/kg
SKN	RBT	LD50	>20	mg/kg

Relevant effects for mixture:

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

Effect	Route	Basis
Irritation	OPT DRM	Hazardous; calculated
Sensitisation	DRM	Hazardous; calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
FISH	96H LC50	>5000	mg/l

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Insoluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Waste code number: 08 04 09

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3077

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 9

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

R36/38: Irritating to eyes and skin.

R43: May cause sensitisation by skin contact.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DISCLAIMER: The information supplied in the MSDS is correct at the time of writing and date of issue. No warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for particular purpose or course of performance or usage of trade. The user of the material is responsible for ensuring the suitability of this product for application.

