



Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

DOCUMENT GROUP:
DATE:
REVISION DATE:

METAL/REPAIR/SYSTEMS
1ST FEBRUARY 2018
1ST FEBRUARY 2019

VERSION REF:
VERSION NO:
SUPERSEDES DATE:

11635/UPS115XL
2.00
1ST NOVEMBER 2016

MATERIAL SAFETY DATA SHEET

UPS 115 XL EXTENDED LIFE METAL KIT

MANUFACTURER:

UNIQUE POLYMER SYSTEMS LTD,
UNIT 19, LINK BUSINESS CENTRE,
LINK WAY, MALVERN, WORCESTERSHIRE,
WR14 1UQ
UNITED KINGDOM

TELEPHONE NUMBER: +44 (0) 1531 63 63 00

EMAIL: SALES@UNIQUEPOLYMERSYSTEMS.COM

EMERGENCY TELEPHONE NUMBER: +44 (0) 1531 63 63 00

THIS PRODUCT IS A KIT AND SUPPLIED AS A MULTI PART PRODUCT WHICH CONSISTS OF A BASE COMPONENT AND ACTIVATOR COMPONENT. THIS DOCUMENT CONTAINS THE MSDS FOR BOTH BASE AND ACTIVATOR COMPONENTS.

TRANSPORTATION INFORMATION

ACTIVATOR	BASE
UN number: UN 1759 UN proper shipping name Shipping name: CORROSIVE SOLID, N.O.S. (4-TERT-BUTYLPHENOL) Transport hazard class(es) Transport class: 8 Packing group: III Environmental hazards Environmentally hazardous: No Marine pollutant: Yes Special precautions for user Special precautions: No special precautions. Tunnel code: E Transport category: 3	UN number: UN3077 UN proper shipping name Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. Transport hazard class(es) Transport class: 9 Packing group: III Environmental hazards Environmentally hazardous: Yes Marine pollutant: No Special precautions for user Tunnel code: E Transport category: 3

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

DISCLAIMER: The information supplied in the MSDS is correct at the time of writing and date of issue. No warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for particular purpose or course of performance or usage of trade. The user of the material is responsible for ensuring the suitability of this product for application.

SECTION 1: Identification of Substance/ Preparation and Company

- 1.1 Product identifier
UPS 115 XL EXTENDED LIFE METAL ACTIVATOR
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
Aliphatic polyamine hardener blend with inert fillers for repairing metalwork
- 1.3 Details of the supplier of the safety data sheet
Unique Polymer Systems LTD, Unit 19,
Link Business Centre, Link Way,
Malvern, Worcestershire,
WR14 1UQ, United Kingdom
Tel: +44 (0) 1531 63 63 00
Email: sales@uniquepolymersystems.com
- 1.4 Emergency telephone number
+44 (0) 1531 63 63 00 (9am to 5pm)

Section 2: Hazards identification

- 2.1. Classification of the substance or mixture
Classification under CHIP: Xi: R36/38; Sens.: R43; -: R52/53
Classification under CLP: Aquatic Chronic 3: H412; Eye Dam. 1: H318; Repr. 2: H361f; Skin Irrit. 2: H315; Skin Sens. 1A: H317; -: EUH208
Most important adverse effects: Irritating to eyes and skin. May cause sensitisation by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 2.2. Label elements
Label elements:
Hazard statements: EUH208: Contains phenol, styrolised. May produce an allergic reaction.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H318: Causes serious eye damage.
H361f: Suspected of damaging fertility.
H412: Harmful to aquatic life with long lasting effects.
Signal words: Danger

Hazard pictograms:
GHS05: Corrosion
GHS07: Exclamation mark
GHS08: Health hazard



Precautionary statements: P102: Keep out of reach of children.

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

P202: Do not handle until all safety precautions have been read and understood.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P302+352: IF ON SKIN: Wash with plenty of water/
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+313: IF exposed or concerned: Get medical advice.
P333+313: If skin irritation or rash occurs: Get medical advice/attention.
P501: Dispose of contents/container to hazardous or special waste collection point.

Label elements under CHIP:
Hazard symbols: Irritant.



Risk phrases: R36/38: Irritating to eyes and skin.
R43: May cause sensitisation by skin contact.
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Safety phrases: S2: Keep out of the reach of children.
S24: Avoid contact with skin.
S29: Do not empty into drains.
S37: Wear suitable gloves.
Precautionary phrases: Contains phenol, styrolised. May produce an allergic reaction.
2.3. Other hazards
Other hazards: Danger of serious damage to health by prolonged exposure.
PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

FATTY ACIDS, C18-UNSATURATED, DIMERS, OLIGOMERIC REACTION PRODUCTS WITH TALL-OIL FATTY ACIDS

AND TRIETHYLENETETRAMINE

3.2. Mixtures

Hazardous ingredients: -

BENZYL ALCOHOL

EINECS	CAS	CHIP Classification	CI P Classification	Percent
-	6882-29-1	-	Eye Dam. 1: H318; Aquatic Chronic 2: H411; Skin Sens. 1: H317; Skin Irrit. 2: H315	10-30%

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

4-TERT-BUTYLPHENOL

202-679-0	98-54-4	Xi: R38; Xi: R41; Xn: R62	Repr. 2: H361f; Skin Irrit. 2: H315; Eye Dam. 1: H318	1-10%
-----------	---------	---------------------------	---	-------

M-PHENYLENEBIS(METHYLAMINE)

216-032-5	1477-55-0	C: R34; Xn: R20/22; Sens.: R43	Skin Corr. 1B: H314; Acute Tox. 4: H302; Skin Sens. 1: H317; Aquatic Chronic 3: H412; Acute Tox. 4: H332	1-10%
-----------	-----------	--------------------------------	--	-------

TRIMETHYLHEXANE-1,6-DIAMINE

247-063-2	25513-64-8	C: R34; Xn: R22; Sens.: R43	Skin Corr. 1C: H314; Acute Tox. 4: H302; Skin Sens. 1A: H317; Aquatic Chronic 3: H412; Acute Tox. 4: H312	1-10%
-----------	------------	-----------------------------	---	-------

PHENOL, STYROLISED

262-975-0	61788-44-1	Xi: R38; Sens.: R43; N: R51/53	Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	<1%
-----------	------------	--------------------------------	--	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Do not create dust. Evacuate the area immediately. Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Alert the neighbourhood to the presence of fumes or gas.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of dust in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

Hazardous ingredients:

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

FATTY ACIDS, C18-UNSATURATED, DIMERS, OLIGOMERIC REACTION PRODUCTS WITH TALL-OIL FATTY ACIDS AND TRIETHYLENETETRAMINE

Type	Exposure	Value	Population	Effect
DNEL	Dermal	1.1mg/kg	Workers	Local
PNEC	Fresh Water	0.00434 mg/l	Workers	Systemic

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Respiratory protective device with particle filter.

Hand protection: Impermeable gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste

Colour: Grey

Odour: Ammoniacal

Solubility in water: Insoluble

Viscosity: Non-viscous

Boiling point/range°C: >200 Flash point°C: >100

Autoflammability°C: 380 Relative density: 2.4

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

M-PHENYLENEBIS(METHYLAMINE)

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

DERMAL	RAT	LD50	3100	mg/kg
ORL	MUS	LD50	930	mg/kg

2,2'-IMINODIETHYLAMINE

DERMAL	RAT	LD50	1280	mg/kg
ORAL	RAT	LD50	910	mg/kg

PHENOL, STYROLISED

DERMAL	RAT	LD50	>2000	mg/kg
ORL	RAT	LD50	>2000	mg/kg

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT DRM	Hazardous: calculated
Sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

M-PHENYLENEBIS(METHYLAMINE)

DAPHNIA	48H EC50	15.2	mg/l
FISH	96H LC50	>100	mg/l

TRIMETHYLHEXANE-1,6-DIAMINE

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

FISH	96H LC50	1380	mg/l
------	----------	------	------

PHENOL, STYROLISED

DAPHNIA	48H EC50	1-10	mg/l
FISH	96H LC50	14.8	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1759

14.2. UN proper shipping name

Shipping name: CORROSIVE SOLID, N.O.S.
(4-TERT-BUTYLPHENOL)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H332: Harmful if inhaled.

H361f: Suspected of damaging fertility.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

R20/22: Harmful by inhalation and if swallowed.

R22: Harmful if swallowed.

R34: Causes burns.

R36/38: Irritating to eyes and skin.

R38: Irritating to skin.

R41: Risk of serious damage to eyes.

R43: May cause sensitisation by skin contact.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R62: Possible risk of impaired fertility.

DISCLAIMER: The information supplied in the MSDS is correct at the time of writing and date of issue. No warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for particular purpose or course of performance or usage of trade. The user of the material is responsible for ensuring the suitability of this product for application.

DISCLAIMER: The information supplied in the MSDS is correct at the time of writing and date of issue. No warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for particular purpose or course of performance or usage of trade. The user of the material is responsible for ensuring the suitability of this product for application.

SECTION 1: Identification of Substance/ Preparation and Company

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

- 1.2 Product identifier
UPS 115 XL EXTENDED LIFE METAL BASE
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
Aliphatic polyamine hardener blend with inert fillers for repairing metalwork
- 1.3 Details of the supplier of the safety data sheet
Unique Polymer Systems LTD, Unit 19,
Link Business Centre, Link Way,
Malvern, Worcestershire,
WR14 1UQ, United Kingdom
Tel: +44 (0) 1531 63 63 00
Email: sales@uniquepolymersystems.com
- 1.4 Emergency telephone number
+44 (0) 1531 63 63 00 (9am to 5pm)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: Xi: R36/38; Sens.: R43; N: R51/53

Classification under CLP: Acute Tox. 4: H302; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; -: EUH205

Most important adverse effects: Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Label elements:

Hazard statements: EUH205: Contains epoxy constituents. May produce an allergic reaction.

H302: Harmful if swallowed.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

Signal words: Warning

Hazard pictograms:

GHS07: Exclamation mark

GHS09: Environmental



Precautionary statements: P264: Wash skin thoroughly after handling.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/.

P302+352: IF ON SKIN: Wash with plenty of water/.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321: Specific treatment (see information on this label).

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

P501: Dispose of contents/container to hazardous or special waste collection point.

Label elements under CHIP:

Hazard symbols: Irritant.

Dangerous for the environment.



Risk phrases: R36/38: Irritating to eyes and skin.

R43: May cause sensitisation by skin contact.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S2: Keep out of the reach of children.

S24: Avoid contact with skin.

S29: Do not empty into drains.

S37: Wear suitable gloves.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

EINECS	CAS	CHIP Classification	CL P Classification	Percent
500-033-5	25068-38-6	Xi: R36/38; Sens.: R43; N: R51/53	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	10-30%

BISPHENOL F TYPE EPOXY RESIN

500-108-2	28064-14-4	Xi: R36/38; N: R51/53; Sens.: R43	Skin Irrit. 2: H315; Eye Irrit. 2: H319; Skin Sens. 1: H317; Aquatic Chronic 2: H411	10-30%
-----------	------------	-----------------------------------	--	--------

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Not applicable.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol or polymer foam. Dry chemical powder. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method. Refer to section 13 of SDS for suitable method of disposal.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from direct sunlight. Avoid incompatible materials and conditions - see section 10 of SDS.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

Hand protection: Protective gloves.
Eye protection: Safety glasses.
Skin protection: Impermeable protective clothing.
Environmental: Prevent from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste
Colour: Dark grey
Odour: Barely perceptible odour
Evaporation rate: Negligible
Oxidising: Non-oxidising (by EC criteria)
Solubility in water: Insoluble
Viscosity: Highly viscous
Boiling point/range°C: >200 Flash point°C: >150
Relative density: 2.7g/cc

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight, Flames.

10.5. Incompatible materials

Materials to avoid: Strong acids. Strong oxidising agents. Amines. Alkalis.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
ORAL	RBT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

ORL	MUS	LD50	15600	mg/kg
-----	-----	------	-------	-------

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

ORL	RAT	LD50	11400	mg/kg
SKN	RBT	LD50	>20	ml/kg

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT DRM	Hazardous: calculated
Sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
FISH	96H LC50	>5000	mg/l

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Insoluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company. Mixed material, once fully cured, can be disposed as solid waste.

Waste code number: 08 04 09

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com

Copyright, 2017, Unique Polymer Systems LTD Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Unique Polymer Systems LTD products is allowed provided that: (1) the information is copied, in full with no changes unless prior written agreement is obtained from Unique Polymer Systems LTD, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon. This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3077

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: No

14.6. Special precautions for user

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH205: Contains epoxy constituents. May produce an allergic reaction.

H302: Harmful if swallowed.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

R36/38: Irritating to eyes and skin.

R43: May cause sensitisation by skin contact.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DISCLAIMER: The information supplied in the MSDS is correct at the time of writing and date of issue. No warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for particular purpose or course of performance or usage of trade. The user of the material is responsible for ensuring the suitability of this product for application.

Unique Polymer Systems LTD

Unit 19 Link Business Centre, Link Way, Malvern, WR14 1UQ, United Kingdom +44(0) 1531 63 63 00

sales@uniquepolymersystems.com www.uniquepolymersystems.com