



DOCUMENT GROUP: DATE: REVISION DATE: METAL/REPAIR/SYSTEMS 1ST MARCH 2017 1ST MARCH 2018 VERSION REF: VERSION NO: SUPERSEDES DATE: 11635/UPS19002/3A&B 2.00 1ST MARCH 2016

MATERIAL SAFETY DATA SHEET UPS 19002/3 A&B CEMENT KIT

MANUFACTURER:

UNIQUE POLYMER SYSTEMS LTD,
UNIT 1 BANKSIDE INDUSTRIAL ESTATE,
LITTLE MARCLE ROAD, LEDBURY,
HEREFORDSHIRE,
HR8 2DR, UNITED KINGDOM

TELEPHONE NUMBER: +44 (0) 1531 636300
EMAIL: INFO@UNIQUEPOLYMERSYSTEMS.COM

EMERGENCY TELEHONE NUMBER: +44 (0) 1531 636300

THIS PRODUCT IS A KIT AND SUPPLIED AS A MULTI PART PRODUCT WHICH CONSISTS OF A BASE COMPONENT AND ACTIVATOR COMPONENT. THIS DOCUMENT CONTAINS THE MSDS FOR BOTH BASE AND ACTIVATOR COMPONENTS.

TRANSPORTATION INFORMATION

ADR: UN 1759, POLYAMINES, SOLID, CORROSIVE, N.O.S. (CONTAINS TRIETHYLENE TETRAMINE,
DIETHYLENETRIAMINE, 8, III, NOT EHS, HIN 80 TUNNEL CODE E, NOT APPLICABLE

IMDG: UN 1759, POLYAMINES, SOLID, CORROSIVE, N.O.S. (CONTAINS TRIETHYLENE TETRAMINE,
DIETHYLENETRIAMINE, 8, III, NOT EHS, EMS F-A, S-B, NOT APPLICABLE

ICAO: UN 1759, POLYAMINES, SOLID, CORROSIVE, N.O.S. (CONTAINS TRIETHYLENE TETRAMINE,
DIETHYLENETRIAMINE, 8, III, NOT EHS, NON, NOT APPLICABLE

ADR: UN 3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOILD, N.O.S. (EPOXY RESIN), 9, III,
ENVIRONMENTALLY HAZARDOUS, HIN 90, NOT APPLICABLE

IMDG: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (EPOXY RESIN), 9, III,
MARINE POLLUTANT, EMS F-A, S-F, NOT APPLICABLE

ICAO: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (EPOXY RESIN), 9, III,
ENVIRONMENTALLY HAZARDOUS, NONE, NOT APPLICABLE





DISCLAIMER: The information supplied in the MSDS is correct at the time of writing and date of issue. No warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for particular purpose or course of performance or usage of trade. The user of the material is responsible for ensuring the suitability of this product for application.

SECTION 1: Identification of Substance/ Preparation and Company

1.1 **Product identifier**

UPS 19002/3 A&B CEMENT ACTIVATOR

1.2 Relevant identified uses of the substance or mixture and uses advised against

Aliphatic polyamine hardener blend with inert fillers for repairing metalwork

1.3 Details of the supplier of the safety data sheet

Unique Polymer Systems LTD, Unit 1 Bankside Industrial Estate, Ledbury, Herefordshire, HR8 2DR

Tel: +44 (0) 1531 636300

Email: info@uniquepolymersystems.com

1.4 **Emergency telephone number** +44 (0) 1531 636300 (9am to 5pm)

SECTION 2: Hazards Identification

2.1 Classification of the substance or mixture

Classification in accordance with the Dangerous Preparations Directive 1999/45/EC

Xn; R20/21/22 Harmful by inhalation, in contact with skin and if swallowed

C; R34 Causes burns

R43 May cause sensitisation by skin contact

Possible risk of irreversible effects Muta. 3; R68 Possible risk of impaired fertility Repr. 2; R62

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic R52/53

environment

Classification in accordance with the Classification Labelling and Packaging Regulation EC (no) 1272/2008

Harmful if swallowed Acute Toxicity Category 4 H302

... for Solutions Acute Toxicity Category 4 4 H312 Harmful in contact with skin

Acute Toxicity Category 4 H332 armful if inhaled

Skin Corrosive Category 1B H314 Causes severe skin burns and eye damage

Eye Damage Category 1 H318 Causes serious eye damage

Skin Sensitiser Category 1 H317 May cause an allergic skin reaction

merSystems.com

The Engineer's Choice





Mutagen Category 2 H341 Suspected of causing genetic defects
Reproductive Toxicity Category 2 H361f Suspected of damaging fertility

Aquatic Chronic Category 3 H412 Harmful to aquatic life with long lasting effects

2.2 Label elements

Labelling in accordance with the Classification Labelling and Packaging Regulation EC (no) 1272/2008 Pictograms:



Signal Word: DANGER

Hazard statements: H302 + H312 + H332: Harmful if swallowed, in contact with skin or if inhaled.

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction. H341: Suspected of causing genetic defects . H361f: Suspected of damaging fertility.

H412 Harmful to aquatic life with long lasting effects

Precautionary statements: P202: Do not handle until all safety precautions have been read and understood.

P280: Wear protective gloves/protective clothing/eye protection/face protection .

The Engineer's Choice

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a doctor

P501: Dispose of contents/container as hazardous waste

2.3 Other hazards

May cause chemical burns to the eyes and skin, and if ingested, to the gastrointestinal tract. May cause allergic skin reaction. Prolonged or repeated exposure may result in adverse effects on fertility.

If released into watercourses in sufficient quantities may be harmful to aquatic life. None of the components are considered to be Persistent, Bioaccumulative and Toxic (PBT) or very Persistent, very Bioaccumulative (vPvB).

SECTION 3: Composition/Information on Ingredients





3.1 Substances

Not applicable, product is a mixture.

3.2 Mixtures

Contains the following hazardous components above thresholds of concern:

Hazardous Components	Cas Number	%	Classification according to Regulation (EC) No 1272/2008	Classification according to Directive 67/548/EEC
Formaldehyde polymer	32610-77-8	10-30%	Acute Tox. 4 H302 Acute Tox.4	Xn; R21/22, R43
with Phenol and			H312, Skin Corr. 1B, skin Sens. 1	C; R34
Triethylenetetramine			H317Aquatic Chronic 3 H412	R52/53
Phenol	108-95-2	<10%	Acute Tox. 3 H301, Acute Tox. 3	Muta. Cat. 3; R68
			H311, Acute Tox. 3 H331	T; R23/24/25
			Skin Corr. 1B H314, Muta. 2	Xn; R48/20/21/22
			H341, STOT RE 2 H373	C; R34
Triethylenetetramine	112-24-3	<10%	Acute Tox. 4 H312, Skin Corr.	Xn; R21, R43
			1B H314, Skin Sens. 1 H317,	C; R34
			Aquatic Chronic 3 H412	R52/53
2,2 iminodiethylamine	111-40-0	<10%	Acute Tox. 4 H302, Acute Tox. 4	T+; R26
	/		H312, Acute Tox. 2 H330, Skin	Xn; R21/22
			Corr. 1B H314, Skin Sens. 1	C; R34
V	2		H317, Eye Dam. 1 H318 , STOT	Xi; R37, R43
			SE 3 H335,	
Bisphenol A	80-05-7	<10%	Skin Sens. 1 H317, Eye Dam. 1	Repr. Cat. 3; R62
			H318, STOT SE 3 H335, Repr. 2	Xi; R37-41, R43
	4		H361f, Aquatic Chronic 2 H411	R52

See section 16 for full description of R phrases and H statements.

SECTION 4: First Aid Measures

... for Solutions

he Engineer's Choice

4.1 Description of first aid measures

Summon immediate medical assistance after contact with skin, eyes, inhalation or ingestion

Eye: Flush eyes with plenty of running water for 15 minutes, whilst gently holding the

eyelids open. Seek immediate medical attention.





Skin: Remove product and contaminated clothing and wash area with water, seek

medical advice. Except in most minor, superficial or localized burns, cover the affected area with a sterile dressing or clean sheeting. DO NOT APPLY GREASES

OR OINTMENTS. Wash contaminated clothing before re-use.

Ingestion: Drink plenty of water, DO NOT INDUCE VOMITING. Seek medical attention

immediately.

Inhalation: Remove patient to fresh air. If breathing has stopped give assisted respiration.

Prevent aspiration of vomit. Turn victims head to one side. Seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Eye Contact: Sign/ Symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Skin Contact: Sign/ Symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration and tissue destruction. Maybe absorbed through skin and cause target organ effects. Persons previously sensitized to amines may develop a cross sensitization reaction to certain other amines

Inhalation: Sign/ Symptoms may include cough, sneezing, nasal discharge, tightness of chest, headache, hoarseness and nose and throat pain.

Ingestion: Signs/ Symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting and diarrhea, blood in the faeces.

4.3 Indication of any immediate medical attention and special treatments needed

Symptomatic treatment as required

SECTION 5: Fire Fighting Measures

5.1 Extinguishing media

Ignition will give rise to class B Fire, in case of fire use Water sprays, Dry chemical, CO2 or Alcohol foam

5.2 Special hazards arising from the substance or mixture

May generate toxic, irritating or flammable combustion products, including nitrogen oxides. Combustion in an oxygen starved environment produces toxic products including nitriles and amides. Sudden reaction and fire may result if mixed with an oxidizing agent.

5.3 Advice for fire fighters

Wear Self-contained breathing apparatus, rubber boots, gloves and body suit

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures





Remove all unnecessary personnel from the area. Ventilate the area if possible. Wear suitable protective clothing including chemical resistant gloves and coveralls. If vapour concentrations are high, respiratory protective equipment may be required. See section 8 for more information.

6.2 Environmental precautions

Prevent entry into sewers and watercourses. If product enters sewers or watercourses, inform the appropriate environmental authorities.

6.3 Methods and materials for containment and clearing up

Scrape up and transfer into a suitable container. Wash area with water.

6.4 References to other sections

Refer to section 5, 8 and 13 for protective Measures and Disposal.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Avoid contact with skin, eyes and clothing. Handle in well ventilated area. Avoid breathing vapours. Wash hands after contact.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a cool, well ventilated area. Keep away from oxidizers, heat or flames.

7.3 Specific end uses(s)

No industrial or sector specific guidance available.

SECTION 8: Exposure Controls/ Personal Protection ymerSystems.com

8.1 Control parameters

Substance Name	8 h <mark>our expo</mark> sure limit	15 min exposure limit	Notes, Source
2,2'-Iminodi(ethylamine)	1 ppm, 4.3 mg/m ³		Sk, EH40, 2011
Bisphenol A	10 mg/m ³	_	EH40, 2011
inhalable dust		fo	r Solutions
Phenol	2 ppm, 7.8 mg/m ³	4 ppm, 16 mg/m ³	Sk, EH40, 2011

8.2 Exposure controls

The Engineer's Choice





Engineering controls Adequate ventilation should be provided so that exposure limits are not exceeded.

Respiratory: Avoid Breathing Vapours, Mists or Sprays; Select and use respiratory protection.

Suggested filter type AP2.

Hand Protection Wear suitable chemical resistant gloves recommended for use with corrosive amines.

Nitrile or neoprene gloves may be suitable, but glove manufacturers' specifications should always be checked first. Change gloves in accordance with manufacturer recommendations. If gloves are damaged during use, remove immediately and wash

hands before replacing with new gloves.

Skin Protection: Avoid Skin Contact; use disposable coveralls

Eye Protection: Avoid Eye Contact; use safety goggles meeting the requirements of BS EN166 3, when

handling this product

Environmental Exposure controls Take suitable measures to prevent entry into drains, sewers and watercourses.

SECTION 9: Physical/ Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: Light Brown Paste

Odour: Ammoniacal, Fishy

Odour threshold: No data
PH: Alkaline
Melting Point: >180C
Boiling Point/ Range: >200C
Flash Point; >100C
Evaporation Rate: No data

UniquePolymerSystems.com

Flammability: Not applicable

Upper/lower flammability limits: No data
Vapour Pressure:
Vapour density:
No data

Relative density: 1.7g/cm3 at 20C
Solubility in water: Insoluble in water

Solubility in other solvents:

Partition Coefficient:

Autoignition temperature:

Decomposition temperature:

Viscosity:

No data

No data

No data

... for Solutions

The Engineer's Choice





Explosive properties: Not classified as explosive **Oxidising properties:** Not classified as oxidising

9.2 Other information

None.

SECTION 10: Stability And Reactivity

10.1 Reactivity

Not considered to be a reactive product

10.2 Chemical stability

Stable

10.3 Possibility of hazardous reactions

Hazardous Polymerisation is not likely to occur.

10.4 Conditions to avoid

Excessive heat.

10.5 Incompatible materials

Oxidising agents – cleaning solutions. Acids - reaction accompanied by large heat release occurs when the product is mixed with acids

10.6 Hazardous decomposition products

Ammonia when heated. Nitrogen Oxides in a fire. Combustion in an oxygen starved environment produces toxic products including nitriles and amides

SECTION 11: Toxicological Information

11.1 Information on toxicological effects QuePolymerSystems.com

The Engineer's Choice

This product has not been tested. Judgements on the expected toxicity of this product have been made based upon consideration of its major components.

(a) acute toxicity	Based on consideration of the components, the mixture is expected to be	
	harmful by inhalation, ingestion or in contact with skin.	
(b) skin corrosion/irritation	Based on consideration of the components, the mixture is expected to be	
	corrosive to skin.	





(c) serious eye damage/irritation	Based on consideration of the components, the mixture is expected to be corrosive to eyes.
(d) respiratory/skin sensitisation	The product contains the following known sensitisers. Formaldehyde polymer with Phenol and Triethylenetetramine, Triethylentetramine, 2,2 iminodiethylamine (diethylenetetramine), bisphenol A, Persons previously sensitized to amines may develop a cross sensitization reaction to certain other amines.
(e) germ cell mutagenicity	The product contains phenol, which is classified as a suspected mutagen.
(f) carcinogenicity	Contains no substances identified as carcinogens.
(g) reproductive toxicity	The product contains bisphenol A which is suspected of damaging fertility.
(h) STOT-single exposure	This product is corrosive, and is expected to irritate the respiratory tract if inhaled.
(i) STOT-repeated exposure	The product contains phenol, which may cause adverse effects to the liver and kidneys if exposed to significant amounts over a prolonged period of time, at a concentration below the classification threshold for this effect.
(j) aspiration hazard	Not applicable.

SECTION 12: Ecological Information

This product has not been tested. Judgements on the expected toxicity of this product have been made based upon consideration of its major components.

12.1 Toxicity

This product contains components which are considered to be harmful to aquatic organisms and may cause long-term adverse effects in the aquatic environment. Once cured the toxicity of the product is expected to decrease.

12.2 Persistence and degradability

This product is not expected to be readily biodegradable.

12.3 Bioaccumulative potential

This product is expected to have a low bioaccumulation potential.

12.4 Mobility in soil

Cured product is expected to be immobile.

12.5 Results of PBT and vPvB assessment

None of the components are known to be PBT or vPvB.

The Engineer's Choice

quePolymerSystems.com

... for Solutions

12.6 Other adverse effects

None known.





SECTION 13: Disposal Considerations

13.1 Waste treatment methods

In uncured state, dispose as chemical waste in accordance with local regulations. Waste from this product may present long term environmental hazards. Thus landfill sites must be considered less acceptable than incineration.

In cured state when mixed correctly with the base component, dispose as solid waste

Empty containers should be disposed of as chemical waste.

SECTION 14: Transport Information

General: Transport and labelling requirements will alter depending on the size of the packaging. Please refer to local transport regulations.

	ADR	IMDG	ICAO
14.1 UN Number	1759	1759	1759
14.2 UN Proper shipping	Polyamines, solid,	Polyamines, solid,	Polyamines, solid,
name	corrosive, N.O.S. (Contains	corrosive, N.O.S. (Contains	corrosive, N.O.S. (Contains
	Triethylene tetramine,	Triethylene tetramine,	Triethylene tetramine,
	Diethylenetriamine)	Diethylenetriamine)	Diethylenetriamine)
14.3 Transport hazard	8	8	8
class(es)			
14.4 Packing group	III	III	III
14.5 Environmental	Not EHS	Not EHS	Not EHS
hazards	7		
14.6 Special precautions	HIN 80	EmS F-A, S-B	None
for user	Tunnel Code E		
14.7 Transport in bulk	Not applicable	Not applicable O Mersys	Not applicable
according to Annex II of	Uniquel	łolymerSys	tems.com
MARPOL 73/78 and the	09401	0.30.030	
IBC Code			
The Engineer's Choice			
CECTION 15. Dogulaton	. Lafa was aki a s		

SECTION 15: Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture 15.1 ... IUT SOIUTIONS

All components are listed as existing substances in Europe

All components are listed, or are exempt from listing on the TCSA Inventory





15.2 **Chemical Safety Assessment**

A Chemical Safety Assessment has not been carried out for this product.

SECTION 16: Other Information

Revision information:

Reformatted in accordance with Regulation 453/2010 and Regulation 1272/2008.

List of Abbreviations used in this SDS:

CAS	Chemical Abstracts Service
LAN	Chemical Angliació Service

CLP Classification, Labelling and Packaging Regulation (EC) no 1272/2008

DSD Dangerous Substances Directive 67/548/EEC DPD Dangerous Preparations Directive 1999/45/EC

EC European Community/Commission PBT Persistent, Bioaccumulative and Toxic

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) no 1907/2006

vPvB very Persistent, very Bioaccumulative

References:

ECHA Classification and Labelling inventory ECHA database of disseminated registration dossiers Supplier's Safety Data Sheets

Method used for classification of mixtures:

Ingredient based approaches

R Phrases and H Statements used in Section 3

Harmful by inhalation and if swallowed, OlymerSystems.com R20/22

Harmful in contact with skin and if swallowed, R21/22

Harmful if swallowed, **R22**

Toxic by inhalation, in contact with skin and if swallowed, R23/24/25;

R26 Very toxic if inhaled R34 Causes burns

... for Solutions R36 Irritating to eyes

R36/38 Irritating to eyes and skin, R37 Irritating to respiratory system, R41 Risk of serious damage to eyes,

R43 May cause sensitisation by skin contact





N40/20/21/22,	narmidi. Danger of serious damage to health by prolonged exposure through inhalation, in contact
	with skin and if swallowed.

R52	Harmful to aquatic organisms
	The state of the s

R52/53 Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment,

R62 Possible risk of impaired fertility
R68 Possible risk of irreversible effects

H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skir

H314	Causes severe skin burns and	eye damage

H317	May cause an allergic skin reaction
H318	Causes serious eye damageH319

H330	Fatal if inhaled
H331	Toxic if inhaled
H332	Harmful if inhaled

H335	May cause respiratory irritation
H341	Suspected of causing genetic defects
110646	

H361f Suspected of damaging fertility

H373 May cause damage to organs through prolonged or repeated exposure

H411 Toxic to aquatic life with long lasting effects
H412 Harmful to aquatic life with long lasting effects

Harmful to aquatic life with long lasting effects
UNIQUEPOLYMERS ystems.com

Training requirements for workers

No special training requirements.

The Engineer's Choice

... for Solutions





SECTION 1: Identification of Substance/ Preparation and Company

1.2 Product identifier

UPS 19002/3 A&B CEMENT BASE

1.2 Relevant identified uses of the substance or mixture and uses advised against Epoxy Resin with inert metallic fillers

1.3 Details of the supplier of the safety data sheet

Unique Polymer Systems LTD, Unit 1 Bankside Industrial Estate, Ledbury, Herefordshire, HR8 2DR

Tel: +44 (0) 1531 636300

Email: info@uniquepolymersystems.com

1.4 Emergency telephone number +44 (0) 1531 636300 (9am to 5pm)

SECTION 2: Hazards Identification

2.1 Classification of the substance or mixture

Classification in accordance with the Dangerous Preparations Directive 1999/45/EC

Xi; R36/38 Irritating to eyes and skin

R43 May cause sensitisation by skin contact

N; R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment

Classification in accordance with the Classification Labelling and Packaging Regulation EC (no) 1272/2008

Skin Irritant Category 2 H315 Causes skin irritation

Eye Irritant Category 2 H319 Causes serious eye irritation

Skin Sensitiser Category 1 H317 May cause an allergic skin reaction

Aquatic Chronic Category 2 H411 Toxic to aquatic life with long lasting effects

2.2 Label elements

Labelling in accordance with the Classification Labelling and Packaging Regulation EC (no) 1272/2008



... for Solutions

olymerSystems.com

Pictograms:

Signal Word: WARNING





Hazard statements: H315 Causes skin irritation

H319 Causes serious eye irritation

H317 May cause an allergic skin reaction

H411 Toxic to aquatic life with long lasting effects

Precautionary statements: P280: Wear protective gloves/protective clothing/eye protection/face protection .

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 If eye irritation persists: Get medical advice/attention.

P501: Dispose of contents/container as hazardous waste

2.3 Other hazards

May cause irritation to the eyes and skin, and if ingested, to the gastrointestinal tract. May cause allergic skin reaction. If released into watercourses in sufficient quantities may be toxic to aquatic life. None of the components are considered to be Persistent, Bioaccumulative and Toxic (PBT) or very Persistent, very Bioaccumulative (vPvB).

SECTION 3: Composition/Information on Ingredients

3.1 Substances

Not applicable, product is a mixture.

3.2 Mixtures

Contains the following hazardous components above thresholds of concern:

Hazardous Components	Cas Number	%	Classification according to	Classification according to
			Regulation (EC) No 1272/2008	Directive 67/548/EEC
Reaction product	28064-14-4	10-30%	Skin Irrit. 2 H315, Skin Sens. 1	Xi; R38-43-51/53
Bisphenol F-			H317,	
(epic <mark>hl</mark> orhydrin)	4		Aquatic Chronic 2 H411	
Reac <mark>tio</mark> n product	25068- <mark>38-6</mark>	10-30%	Skin Irrit. 2 H315, Eye Irrit. 2	Xi; R36/38-43-51/53
bisph <mark>enol</mark> -A-			H319, Skin Sens. 1 H317,	0. 0 00.00
(epichl <mark>orhyd</mark> rin) epoxy			Aquatic Chronic 2 H411	
resin (number average				
molecular weight <=			for	· Solutions
700)			101	001410110

See section 16 for full description of R phrases and H statements.

SECTION 4: First Aid Measures





4.1 Description of first aid measures

Summon immediate medical assistance after contact with skin, eyes, inhalation or ingestion

Eye: Flush eyes with plenty of running water for several minutes, whilst gently

holding the eyelids open. Seek medical attention if irritation persists.

Skin: Remove product and contaminated clothing and wash area with water, seek

medical advice. Wash contaminated clothing before re-use.

Ingestion: Drink plenty of water, DO NOT INDUCE VOMITING. Seek medical attention

immediately.

Inhalation: Remove patient to fresh air. If breathing has stopped give assisted respiration.

Prevent aspiration of vomit. Turn victims head to one side. Seek medical advice.

The Engineer's Choice

... for Solutions

4.2 Most important symptoms and effects, both acute and delayed

Eye Contact: Sign/ Symptoms may include redness, tearing, pain.

Skin Contact: Sign/ Symptoms may include localised redness, swelling, itching

Inhalation: Sign/ Symptoms may include cough, sneezing, nasal discharge, tightness of chest, headache,

hoarseness and nose and throat irritation.

Ingestion: Signs/ Symptoms may include irritation of the mouth, throat, nausea, vomiting.

4.3 Indication of any immediate medical attention and special treatments needed

Symptomatic treatment as required

SECTION 5: Fire Fighting Measures

5.1 Extinguishing media

Ignition will give rise to class B Fire, in case of fire use Water sprays, Dry chemical, CO2 or Alcohol foam

5.2 Special hazards arising from the substance or mixture METS/STEMS.COM

Sudden reaction and fire may result if mixed with an oxidizing agent.

5.3 Advice for fire fighters

Wear Self-contained breathing apparatus, rubber boots, gloves and body suit

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all unnecessary personnel from the area. Ventilate the area if possible. Wear suitable protective clothing including chemical resistant gloves and coveralls. If vapour concentrations are high, respiratory protective equipment may be required. See section 8 for more information.





6.2 Environmental precautions

Prevent entry into sewers and watercourses. If product enters sewers or watercourses, inform the appropriate environmental authorities.

6.3 Methods and materials for containment and clearing up

Scrape up and transfer into a suitable container. Wash area with water.

6.4 References to other sections

Refer to section 5, 8 and 13 for Protective Measures and Disposal.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Avoid contact with skin, eyes and clothing. Handle in well ventilated area. Avoid breathing vapours. Wash hands after contact.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a cool, well ventilated area. Keep away from oxidizers, heat or flames.

7.4 Specific end uses(s)

No industrial or sector specific guidance available.

SECTION 8: Exposure Controls/ Personal Protection

8.1 Control parameters

Substance Name	8 hou <mark>r exposu</mark> re limit	15 min exposure limit	Notes, Source
Talc (magnesium silicate), respirable dust	1 mg/m³	The Engine	EH40, 2011

8.2 Exposure controls

dequate ventilation should be provided so that exposure limits are not exceeded

JniquePolymerSystems.com

Respiratory:Adequate ventilation should be provided so that exposure limits are not exceeded.
Not normally required. If significant aerosols are liley to be generated a suitable respirator may be required. Suggested filter type AP2.

... for Solutions





Hand Protection Wear suitable chemical resistant gloves. Nitrile or neoprene gloves may be suitable, but

> glove manufacturers' specifications should always be checked first. Change gloves in accordance with manufacturer recommendations. If gloves are damaged during use,

remove immediately and wash hands before replacing with new gloves.

Skin Protection: Avoid Skin Contact; use disposable coveralls

Eye Protection: Avoid Eye Contact; use safety goggles meeting the requirements of BS EN166 3, when

handling this product

Environmental Exposure controls Take suitable measures to prevent entry into drains, sewers and watercourses.

SECTION 9: Physical/ Chemical Properties

Information on basic physical and chemical properties 9.1

Appearance: Dark Grey Paste

Odour: Weak Odour threshold: No data PH: Neutral **Melting Point:** No data

quePolymerSystems.com 170C **Boiling Point/ Range:**

Flash Point; >150C No data **Evaporation Rate:**

The Engineer's Choice Flammability: Not applicable

Upper/lower flammability limits: No data Vapour Pressure: No data Vapour density: No data

... for Solutions

Relative density: 1.7g/cm3 at 20C Solubility in water: Insoluble in water

Solubility in other solvents: Soluble in organic solvents

Partition Coefficient: Log Kow 3-5 (estimated) (Bisphenol A/F epoxy resin)

Autoignition temperature: Above boiling point





Decomposition temperature: No data **Viscosity:** Thick paste

Explosive properties: Not classified as explosive **Oxidising properties:** Not classified as oxidising

9.2 Other information

None.

SECTION 10: Stability And Reactivity

10.1 Reactivity

Not considered to be a reactive product

10.2 Chemical stability

Stable

10.3 Possibility of hazardous reactions

Hazardous Polymerisation is not likely to occur.

10.4 Conditions to avoid

Excessive heat.

10.5 Incompatible materials

Acids - reaction accompanied by large heat release occurs when the product is mixed with acids

10.6 Hazardous decomposition products

None identified.

SECTION 11: Toxicological Information

The Engineer's Choice

quePolymerSystems.com

11.1 Information on toxicological effects

This product has not been tested. Judgements on the expected toxicity of this product have been made based upon consideration of its major components.

(a) acute toxicity	Based on consideration of the components, the mixture is not expected to be
,	harmful by inhalation, ingestion or in contact with skin. The ATE for the
	mixture is expected to be >2000 mg/kg





(b) skin corrosion/irritation	Based on consideration of the components, the mixture is expected to be irritating to skin.
(c) serious eye damage/irritation	Based on consideration of the components, the mixture is expected to be irritating to eyes.
(d) respiratory/skin sensitisation	The product contains the following known sensitisers: Bisphenol A epoxy resin, Persons previously sensitized to amines may develop a cross sensitization reaction to certain other amines.
(e) germ cell mutagenicity	Contains no substances identified as mutagens.
(f) carcinogenicity	Contains no substances identified as carcinogens.
(g) reproductive toxicity	Resins based on Bisphenol A did not cause adverse effects in animal tests.
(h) STOT-single exposure	Target organ toxicity is not expected with this product.
(i) STOT-repeated exposure	Target organ toxicity is not expected with this product.
(j) aspiration hazard	Not applicable.

SECTION 12: Ecological Information

This product has not been tested. Judgements on the expected toxicity of this product have been made based upon consideration of its major components.

12.1 Toxicity

This product contains components which are considered to be toxic to aquatic organisms and may cause long-term adverse effects in the aquatic environment. Once cured the toxicity of the product is expected to decrease.

Data for Component: Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

Fish Acute & Prolonged Toxicity

LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 h: 2 mg/l

UniquePolymerSystems.com

Aquatic Invertebrate Acute Toxicity

EC50, Daphnia magna (Wa<mark>ter flea)</mark>, static test, 48 h, immobilization: 1.8 mg/l — S C C C C C Aquat<mark>ic Plant Toxicity</mark>

ErC50, Scenedesmus capricornutum (fresh water algae), static test, Growth rate inhibition, 72 h: 11 mg/l

Toxicity to Micro-organisms

IC50; Bacteria, 18 h: > 42.6 mg/l

Aquatic Invertebrates Chronic Toxicity Value

Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, NOEC: 0.3 mg/l

12.2 Persistence and degradability

... for Solutions





This product is not expected to be readily biodegradable.

Data for Component: Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

Biodegradation	Exposure Time	Method	10 Day Window
12 %	28 d	OECD 302B Test	Not applicable

12.3 Bioaccumulative potential

This product is expected to have a low-moderate bioaccumulation potential.

12.4 Mobility in soil

Monbility of the uncured product is expected to be low. Cured product is expected to be immobile.

12.5 Results of PBT and vPvB assessment

None of the components are known to be PBT or vPvB.

12.6 Other adverse effects

None known.

SECTION 13: Disposal Considerations

13.1 Waste treatment methods

In uncured state, dispose as chemical waste in accordance with local regulations. Waste from this product may present long term environmental hazards. Thus landfill sites must be considered less acceptable than incineration.

In cured state when mixed correctly with the activator component, dispose as solid waste

Empty containers should be disposed of as chemical waste.

UniquePolymerSystems.com

The Engineer's Choice

... for Solutions

SECTION 14: Transport Information

General: Transport and labelling requirements will alter depending on the size of the packaging. Please refer

to local transport regulations.





	ADR	IMDG	ICAO
14.1 UN Number	3077	3077	3077
14.2 UN Proper shipping	Environmentally	Environmentally	Environmentally
name	hazardous substance,	hazardous substance,	hazardous substance,
	solid, N.O.S. (epoxy resin)	solid, N.O.S. (epoxy resin)	solid, N.O.S. (epoxy resin)
14.3 Transport hazard	9	9	9
class(es)			
14.4 Packing group	III	III	III
14.5 Environmental	Environmentally	Marine Pollutant	Environmentally
hazards	hazardous		hazardous
14.6 Special precautions	HIN 90	EmS F-A, S-F	None
for user			
14.7 Transport in bulk	Not applicable	Not applicable	Not applicable
according to Annex II of			
MARPOL 73/78 and the			
IBC Code			

SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

All components are listed as existing substances in Europe

All components are listed, or are exempt from listing on the TCSA Inventory

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out for this product.

SECTION 16: Other Information

Revision information:

Reformatted in accordance with Regulation 453/2010 and Regulation 1272/2008.

List of Abbreviations used in this SDS:

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging Regulation (EC) no 1272/2008

DSD Dangerous Substances Directive 67/548/EEC

DPD Dangerous Preparations Directive 1999/45/EC

... for Solutions

olymerSystems.com

EC European Community/Commission





PBT Persistent, Bioaccumulative and Toxic

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) no 1907/2006

vPvB very Persistent, very Bioaccumulative

References:

ECHA Classification and Labelling inventory ECHA database of disseminated registration dossiers Supplier's Safety Data Sheets

Method used for classification of mixtures:

Ingredient based approaches

R Phrases and H Statements used in Section 3

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

R36/38 Irritating to eyes and skin.

R38 May be irritating to skin

R43 May cause sensitization by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Training requirements for workers

No special training requirements.

